




En Color:
NATURAL


Cangilón RD Lufelo
reforzado para
trabajo pesado

convenciones

vista lateral



vista frontal



Temperatura
Máxima de uso 80° C.

CANGILÓN RD LUFELO

Tipo	A mm	B mm	C mm	D mm	E mm	Diá. Agu.	Cant. Agu.	Capacidad Cm³ x --- x	Peso gr.	Esp.
4" x 3 RD	108	57	83	75	45	1/4	2	240	78	6
4" x 4 RD	104	50	95	80	50	1/4	2	315	92	5
5" x 4 RD	135	81	110	100	65	1/4	2	590	210	7
6" x 4 RD	163	98	110	100	65	1/4	2	724	238	8
6" x 5 RD	160	98	135	125	70	1/4	2	1.100	305	8
7" x 4 RD	188	120	115	125	70	1/4	2	840	266	8
7" x 5 RD	180	120	140	125	80	1/4	2	1.300	397	8
8" x 5 RD	208	78	145	120	80	1/4	3	1.500	337	8
8" x 6 RD	210	78	170	140	100	5/16	3	2.200	650	8
9" x 5 RD	242	89	145	130	85	5/16	3	1.800	508	8
9" x 6 RD	235	88	170	150	110	5/16	3	2.462	700	8
10" x 6 RD	260	90	165	150	110	5/16	3	2.800	780	8
10" x 7 RD	264	90	195	180	120	5/16	3	3.950	1.100	10
11" x 6 RD	288	76	165	150	110	5/16	4	3.035	860	8
11" x 7 RD	288	76	195	180	130	5/16	4	4.400	1.150	8
12" x 7 RD	315	86	200	180	130	5/16	4	4.800	1.350	10
13" x 8 RD	345	92	220	195	140	5/16	4	7.450	1.550	10
14" x 7 RD	360	95	190	170	120	5/16	4	4.370	1.280	10
16" x 8 RD	420	85	212	195	140	5/16	5	7.600	1.700	10

TABLA TÉCNICA



MATERIALES
DE ALTA CALIDAD



ALTA RESISTENCIA
Y DURABILIDAD



FABRICACIÓN
SOBRE PEDIDO



EXCELENTE
DESEMPEÑO

MATERIALES DE ALTA CALIDAD Y RESISTENCIA

HECHO EN MEDELLÍN / COLOMBIA